

What is claimed is:

1 1. A laundry dryer having a sealing assembly for a hinged door, the laundry
2 dryer comprising:

3 a door frame, said door frame being provided with a door glass;

4 a frame cover having a frame cover panel in which an entrance hole is formed for
5 receiving said door frame, the frame cover panel having an inner end surface;

6 a front support, coupled with said frame cover, for supporting a drum, the front
7 support having a front support panel having an inner end surface; and

8 a unified sealing member, fixed to the inner end surfaces of the frame cover panel and
9 front support panel, providing for simultaneous contact with surfaces of said door frame and
10 said door glass when the hinged door is closed.

1 2. The laundry dryer as claimed in claim 1, said unified sealing member
2 comprising:

3 a small diameter part for receiving an inner end of the frame cover panel;

4 a large diameter part, disposed so as to create a space with respect to said small
5 diameter part, the created space for receiving the inner end surfaces of the frame cover panel
6 and front support panel;

7 a tip, protruding from a juncture of said large diameter part and small diameter part,
8 said tip being in pliant contact with said door frame when the hinged door is closed; and

9 a lip, protruding from one side of said large diameter part, said lip being in pliant
10 contact with the door glass of said door frame when the hinged door is closed.

1 3. The laundry dryer as claimed in claim 2, wherein the inner end of the frame
2 cover panel of said frame cover is formed as a rolled inner end.

1 4. The laundry dryer as claimed in claim 3, wherein the rolled inner end is
2 curved toward said door frame.

1 5. The laundry dryer as claimed in claim 4, further comprising a fixing bar for
2 pressing and fixing said small diameter part of said unified sealing member to the rolled inner
3 end of the frame cover panel of said frame cover.